



LOC	DIST	REVISIONS					
		P	LTR	DESCRIPTION	DATE	DWN	APVD
GP	00						
			D1	REVISED PER ECO-11-004835	11MAR11	RK	HMR

D



TERMINATED VIEW

C



HOUSING

CONTACT


COVER

A SPACES AT .050 STAGGERED SPACING
= B REF


POSN #1 INDICATOR

SEE DETAIL Z

B



.629 REF
BEFORE
TERMINATION



DETAIL Z
SCALE 10:1
TYPICAL

OBSOLETE

3.100	3.380	3.150	63	64	1-1658620-2
2.900	3.180	2.950	59	60	1-1658620-1
2.400	2.680	2.450	49	50	1-1658620-0
1.900	2.180	1.950	39	40	1658620-9
1.600	1.880	1.650	33	34	1658620-8
1.400	1.680	1.450	29	30	1658620-7
1.200	1.480	1.250	25	26	1658620-6
1.100	1.380	1.150	23	24	1658620-5
.900	1.180	.950	19	20	1658620-4
.700	.980	.750	15	16	1658620-3
.600	.880	.650	13	14	1658620-2
.400	.680	.450	9	10	1658620-1
D	C	B	A	NO OF POSN	PART NUMBER

A

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN R. SAMICK 22AUG03	TE Connectivity		
DIMENSIONS: INCHES		CHK C. ROHDE 22AUG03			
		APVD M. WALMSLEY 22AUG03	NAME		
		PRODUCT SPEC 108-40000	RECEPTACLE ASSY, MILITARY POLARIZATION, LEAD FREE, AMP-LATCH™ NOVO		
TOLERANCES UNLESS OTHERWISE SPECIFIED:		APPLICATION SPEC 114-40005	SIZE A2	CAGE CODE 00779	DRAWING NO C=1658620
MATERIAL		WEIGHT -	RESTRICTED TO -		
FINISH		CUSTOMER DRAWING	SCALE 4:1	SHEET 1 of 1	REV D1

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[1658620-2](#)